

Hydraulic power tools

Able to customize bender



REBAR BENDERS

TR-25X REBAR BENDER

[v-TR-25X.mp4](#)

Model number : TR-25X
Electric Voltage : 110V/220V 50/60Hz
Electric Current : 11A / 5.5A
Max.Rebar Diameter : Φ 25 mm
Weight : 25 kg
Bending Force : 15 t
Size (L x W x H) : 610 x 240 x 210 mm

TR-32X REBAR BENDER

[v-TR-32X.mp4](#)

Model number : TR-32X
Electric Voltage : 110V/220V 50/60Hz
Electric Current : 14A / 7A
Max.Rebar Diameter : Φ 32 mm
Weight : 38 kg
Bending Force : 30 t
Size (L x W x H) : 643 x 277 x 255 mm



TR-32 REBAR STRAIGHTENER

[v-TR-32.mp4](#)

Model number : TR-32
Electric Voltage : 110V/220V 50/60Hz
Electric Current : 11A / 5.5A
Max.Rebar Diameter : Φ 32 mm
Weight : 21 kg
Bending Force : 15 t
Size (L x W x H) : 540 x 325 x 210 mm



TR-50 REBAR STRAIGHTENER

[v-TR-50.mp4](#)

Model number : TR-50
Electric Voltage : 110V/220V 50/60Hz
Electric Current : 14A / 7A
Max.Rebar Diameter : Φ 50 mm
Weight : 38 kg
Bending Force : 30 t
Size (L x W x H) : 610 x 340 x 264 mm



TR-16 REBAR BENDER

[v-TR-16.mp4](#)

Model number : TR-16
Electric Voltage : 110V/220V 50/60Hz
Electric Current : 11A / 5.5A
Bending Diameter : Φ 9 ~ Φ 16 mm
Bending Speed : 4 sec
Bending Angle(Degrees) : 0 ~ 160 °
Weight : 16.5 kg
Size (L x W x H) : 545 x 155 x 183 mm

